

**LIME
+ SANITARY**



LIME + SANITARY

Removes lime and inorganic dirt from kitchens, bathrooms, and sanitary areas. Perfect for deep cleaning wet areas.

SUITABLE FOR

Tiles

Showers

Toilets

Faucets

Drains



AVAILABLE AS

2x0.4L Twin Sprayer Set

4x0.4L Reload Set

2x5L Set



WSP

WHITE STONE PATTAYA

www.whitestonepattaya.com
contact@whitestonepattaya.com



Product Data Sheet

arvox ^{PRO}

LIME & SANITARY

APPLICATION

Preparation: Remove coarse dirt from the surface. Cover areas that should not be treated if necessary. May affect galvanized metals. Test surface compatibility in an inconspicuous spot. Use only clean spray heads or pressure sprayers.

Application: Quickly spray Arvox Pro A and B on the surface to be cleaned, ensuring even coverage. Work in small sections. Allow Arvox to sit briefly and then work in with a soft sponge or pad. For machine application, use a single-disc machine with a suitable cleaning pad. Collect the dirt solution. Rinse or wipe with clear water.
Coverage: approx. 4-10m²/L (0.5 L per component) **Please note:** Cover or remove any galvanized parts before application. Spray A & B quickly one after the other, or preferably simultaneously, on the surface. Thoroughly rinse tools/machines and other equipment after use.

HANDLING AND STORAGE

Arvox Pro Lime + Sanitary is stable for at least 24 months when stored in the original container as recommended. Store in a location accessible only to authorized personnel. Keep cool, dark, and upright. Heat, sunlight, and frost can affect the product's effectiveness. Use opened containers within 3 months. Dispose of product remnants and containers according to official regulations.

SAFETY PRECAUTIONS

Standard safety precautions when handling chemicals must be observed. Protective gloves, goggles, clothing, and a mask should be worn. Detailed safety instructions are available in the safety data sheets for Arvox Pro Lime + Sanitary A and B.

DISCLAIMER These details are compiled based on our current knowledge. They do not constitute an assurance of product properties or a legal claim. Given the diverse applications and conditions, we always recommend testing our products for intended uses. Safety data sheets with precautions for handling or storing Arvox Pro products are available upon request and provided in accordance with applicable laws. You should obtain and review the relevant safety data sheet information before handling these products. For further information, please contact White Stone Pattaya CO.,LTD.


MANUAL APPLICATION

The components are worked in using a sponge or pad.



MACHINE APPLICATION

Preferably use orbitally operating cleaning machines and appropriate pads to work in the components.



*>Our recommendation:
Use sprayers with a dual-chamber system to apply both components simultaneously.*



ARVOX PRO A

*Ingredients (according to 1272/2008/EC) none;
(according to 648/2004/EC) anionic surfactants*

Appearance	Clear
Color	Colorless
Scent	Characteristic/Alkaline
Density	1.01 g/cm ³
Dynamic Viscosity	10 mPa.s
pH	7-9

ARVOX PRO B

*(acc. to 1272/2008/EC) Methanesulfonic acid,
Formic acid; (acc. to 648/2004/EC) none*

Appearance	Like Water
Color	Colorless
Scent	Characteristic Acid
Density	1.06 g/cm ³
Dynamic Viscosity	10 mPa.s
pH	2-3

Values measured at 20° C